



# ALLIED PRESSROOM CHEMISTRY

## MATERIAL SAFETY DATA SHEET

### SECTION 1 PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER : **ALLIED LV MRC 100**  
(Low VOC Metering Roller Cleaner for lithographic presses)

MANUFACTURER'S NAME: ALLIED PRESSROOM CHEMISTRY.

STREET ADDRESS  
2040 LEE STREET, HOLLYWOOD, FLORIDA, 33020, USA

OFFICE TELEPHONE:  
800-327-8487

FAX:  
954-923-6462

24 HR. EMERGENCY TELEPHONE  
800-424-9300 CHEMTREC

**THIS IS AN INDUSTRIAL CHEMICAL PRODUCT. ALL INDUSTRIAL CHEMICAL PRODUCTS POSE AN INHERENT HEALTH RISK. BEFORE USE ALWAYS READ COMPLETE LABEL AND MSDS FOR SAFE HANDLING PROCEDURES**

0-minimal, 1-slight, 2-moderate, 3-serious, 4-severe  
HEALTH HAZARD: 2  
FIRE HAZARD: 3  
REACTIVITY: 0  
PROTECTIVE EQUIPMENT: C



Safety Glasses



Gloves



Protective Apron

DO NOT BREATHE VAPORS. DO NOT GET IN EYES, SKIN. DO NOT GET ON CLOTHING. DO NOT INGEST

### SECTION 2 – INGREDIENT INFORMATION

| INGREDIENTS  | %       | CAS NUMBER | HAZARD DATA              |
|--|---------|------------|--------------------------|
| <i>*These ingredients are subject to the reporting requirements of SARA 313 and 40 CFR 372</i> |         |            |                          |
| Acetone  | 30 - 50 | 67-64-1    | ACGIH (TLV) TWA 500 ppm  |
| Methyl Acetate   | 25-40   | 79-20-0    | ACGIH (TWA-TLV) 200 ppm  |
| Halogenated Hydrocarbon  | 10-30   | 98-56-6    | Not Established          |
| 2-Butoxyethanol *  | 1-10    | 111-76-2   | ACGIH (TLV) TWA 25 ppm   |
| Aliphatic Petroleum Naphtha  | 1-10    | 64742-89-8 | ACGIH (TWA-TLV) –100 ppm |

ALL INGREDIENTS ARE LISTED IN THE US TOXIC SUBSTANCE CONTROL ACT (TSCA)

### SECTION 3 - PHYSICAL DATA

|  |   |   |                                 |  |
|--|---|---|---------------------------------|--|
| PHYSICAL STATE<br>LIQUID                           | ODOR AND APPEARANCE<br>Clear colorless liquid,<br>Ketone odor | WATER SOLUBILITY<br>Partial                   | PH<br>Not applicable            | SPECIFIC GRAVITY<br>0.95                                   |
| VAPOR PRESSURE<br>(MM Hg) of VOC<br>< 5mmHg @ 20°C | VAPOR DENSITY<br>(AIR=1)<br>>1                                | EVAPORATION RATE<br>(Butyl acetate = 1)<br><1 | BOILING POINT (°F)<br>132 – 340 | V.O.C.'s less exempt cpds<br>0.68 lb per Gallon<br>82 g/l) |

### SECTION 4 - FIRE AND EXPLOSION DATA

|   |  |   |  |  |
|---|--|---|--|--|
| FLAMMABILITY<br>YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> | IF YES, UNDER WHICH CONDITIONS? * Excess heat, sparks and open flame.        |   |  |  |
| EXTINGUISHING MEDIA<br>CARBON DIOXIDE, DRY CHEMICAL, UNIVERSAL FOAM.                | SPECIAL FIRE FIGHTING PROCEDURES:<br>Use self contained breathing apparatus. |   |  |  |
| FLASHPOINT (°F) AND METHOD<br>< 4 F by TCC  | UPPER FLAMMABLE LIMIT<br>(% BY VOLUME) : Unknown                             | LOWER FLAMMABLE LIMIT<br>(% BY VOLUME): Unknown |  |  |
| AUTOIGNITION TEMPERATURE (°C)<br>Not known  | HAZARDOUS COMBUSTION PRODUCTS<br>Oxides of carbon and hydrocarbons.          |   |  |  |
| EXPLOSION DATA * NOT KNOWN  | SENSITIVITY TO IMPACT - NO   | SENSITIVITY TO STATIC DISCHARGE<br>YES          |  |  |

### SECTION 5 - REACTIVITY DATA

|  |   |  |   |  |
|--|---|--|---|--|
| CHEMICAL STABILITY<br>YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>  | CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERISATION<br>None |  |   |  |
| INCOMPATIBILITY WITH OTHER SUBSTANCES<br>Strong oxidizing agents, strong reducing agents   |   |  |   |  |
| HAZARDOUS DECOMPOSITION PRODUCTS: In contact with open flame or incandescent material will liberate carbon dioxide, carbon monoxide and hydrocarbons |   |  | This product is non- photochemically reactive |  |



# ALLIED PRESSROOM CHEMISTRY

## MATERIAL SAFETY DATA SHEET

PRODUCT IDENTIFIER \* **ALLIED LV MRC 100**

### SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY

SKIN CONTACT ■

SKIN ABSORPTION ■

EYE CONTACT ■

INHALATION ■

INGESTION ■

**ACUTE EXPOSURE TO PRODUCT:** Inhalation - Inhalation can cause severe irritation of the respiratory tract, signs of central nervous system depression, dizziness nausea and headache. Eye - Will cause severe irritation, burning, redness and tearing. Skin - Can cause irritation, redness burning and drying. Ingestion causes irritation of the digestive tract. Aspiration into the lungs can lead to pulmonary odema and chemical pneumonia which can prove fatal. Prolonged over-exposure can lead to narcosis, respiratory failure , coma.

**CHRONIC EXPOSURE TO PRODUCT:** Prolonged skin contact may aggravate an existing dermatitis. Prolonged and repeated exposure to the pure solvent contained in this product has been reported to cause permanent brain and central nervous system damage.

**CARCINOGENICITY:** No ingredient has been identified as carcinogenic or potentially carcinogenic by IARC, NTP, OSHA

**TARGET ORGAN EFFECTS:** Eyes, skin irritation. Kidneys, blood, liver and lung effects on prolonged over-exposure

#### EMERGENCY FIRST AID PROCEDURES:

**EYES:** Flush with running water for at least 15 minutes. Seek medical attention.

**SKIN:** wash affected area with soap and water. Remove contaminated clothing and launder before re-use.

**INHALATION:** Remove victim to fresh air. Administer oxygen and/or artificial respiration if breathing difficulties occur. Seek medical attention.

**INGESTION:** Do not induce vomiting. Material is an aspiration hazard, may enter lungs and cause lung damage. Seek immediate medical attention.

### SECTION 7 - PREVENTATIVE MEASURES

#### GLOVES

Nitrile for incidental, non-immersion contact.

**RESPIRATOR:** Use NIOSH approved SCBA in emergency situations or confined areas.

#### EYE (SPECIFY)

Splash proof goggles or face shield

**CLOTHING :** Boots, aprons , or chemical suits should be used when necessary to prevent skin contact.

**ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) :** Use local exhaust or dilution ventilation as appropriate to control exposure below permissible levels. Vapors are heavier than air and will collect in low areas

**LEAK AND SPILL PROCEDURE:** Extinguish all sources of ignition. Provide maximum ventilation. Dike area to contain spill. Take precautions to prevent contamination of ground and surface waters. Recover spilled material using absorbent material such as vermiculite and sweep into closed containers for disposal.

**WASTE DISPOSAL:** Contaminated vermiculite or porous surface must be disposed of in a permitted hazardous waste facility. Recovered liquids may be reprocessed or incinerated in a permitted hazardous waste facility. In all cases material should be disposed of in accordance with all applicable regulations.

**HANDLING PROCEDURES AND EQUIPMENT:** Keep container closed when not in use. Store only in closed, properly labeled containers. Store as **VERY FLAMMABLE LIQUID**. Store in a cool, dry, well ventilated area away from heat sparks and open flames. Treat empty containers as containing hazardous residues.

### ADDITIONAL INFORMATION

**CALIFORNIA PROPOSITION 65:** *This regulation does not address "de minimis" levels. Therefore even trace amounts of chemicals on these lists must be identified. Trace quantities refer low levels of materials whose exact concentrations may not always be determined because of their minuteness.*

This product contains the following chemicals known by the state of California to cause cancer : benzene, acetaldehyde, formaldehyde, ethylene oxide. This product contains following chemicals known by the state of California to cause reproductive harm : benzene, ethylene oxide

**SHIPPING INFORMATION:** Flammable liquids, NOS (acetone, methyl acetate), 3, UN 1993, PG II

### SECTION 9 - PREPARATION AND DATE OF MSDS

PREPARED BY (GROUP DEPARTMENT, ETC.)

ALLIED PRESSROOM CHEMISTRY TECHNICAL SERVICES DEPARTMENT

PHONE NUMBER

1-800-327-8487

DATE

Sept 2010

The above information is believed to be correct as of the date hereof and is based on data supplied by raw material suppliers, however, no warranty of merchantability, fitness for use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with each use. Since the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its' use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assume risk of his use thereof.